

# SPECIFICATIONS



Models <sup>(1)</sup>	Kilowatts (HP) <sup>(2)</sup>	Max. RPM at full throttle	Cylinders	Displacement	Starting	Gear ratio	Steering	Alternator system	Trim positions	Weight <sup>(4)</sup>	Recommended boat transom height	Induction system	
<b>MARINER FOURSTROKES</b>													
150	150EFI	110.3 (150)	5000 - 5800	4 (in-line)	3000 cc	Electric (turn-key)	1.92:1	Remote	60 amp (756 watt)	Power trim standard	206 kg	508 mm (L) - 635 mm (XL)	4-valve dual overhead cam design
75 - 115	115 EFI - 90 EFI - 75EFI	84.6 (115) - 66.2 (90) - 55.2 (75)	115: 5000 - 6000 90-75: 4500 - 5500	4 (in-line)	2100 cc	SmartStart electric	2.07:1	Remote	35 amp (441 watt)	Power trim standard	115: 165 kg 90: 163 kg 75: 163 kg	115: 508 mm (L) - 635 mm (XL) 90 - 75: 508 mm (L)	4-valve single overhead cam design
40 - 60	60EFI + CT 50 EFI	44.1 (60) - 36.8 (50)	5500 - 6000	4 (in-line)	995 cc	Electric (turn-key)	1.83:1 BIGFOOT: 2.33:1	Remote	18 amp (226 watt)	Power trim standard	112 kg Command Thrust: 118 kg	508 mm (L)	2-valve single overhead cam design
	40 EFI	29.4 (40)	5500 - 6000	3 (in-line)	747 cc	Electric (turn-key)	2.00:1	Remote	18 amp (226 watt)	Power trim standard	98 kg	508 mm (L)	2-valve single overhead cam design
25 - 30	30 <sup>(3)</sup> - 25 EFI <sup>(3)</sup>	22.1 (30) - 18.4 (25)	30: 5250 - 6250 25: 5000 - 6000	3 (in-line)	526 cc	Manual or electric (turn-key)	1.92:1	Tiller or remote	15 amp (186 watt)	30: Gas assist or power trim 25: Power trim	30: 78 kg 25: 71 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design
15 - 20	20 <sup>(3)</sup> - 15 <sup>(3)</sup>	14.7 (20) - 11 (15)	20: 5400 - 6100 15: 5400 - 5600	2 (in-line)	351 cc	Manual or electric	2.51:1	Tiller or remote	12 amp (138 watt)	6 & shallow water drive	52 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design
8 - 9.9	9.9 <sup>(3)</sup> - 8 <sup>(3)</sup>	7.28 (9.9) - 5.88 (8)	5000 - 6000	2 (in-line)	208 cc	Manual or electric	2.08:1	Tiller	6 amp (76 watt) on electric start models	6 & shallow water drive	38 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design
2.5 - 6	6 <sup>(5)</sup> - 5 <sup>(5)</sup> - 4 <sup>(5)</sup> + 5 SAILMATE <sup>(5)</sup>	4.41 (6) - 3.68 (5) - 2.94 (4)	6: 5000 - 6000 5 - 4: 4500 - 5500	1	123 cc	Manual	2.15:1	Tiller	Optional 4 amp (50 watt) lighting, 2 amp (25 watt) charging 5 SAILMATE: Standard with rectifier	6 & shallow water drive	25 kg	381 mm (S) 508 mm (L) 5 SAILMATE: 508 mm (L)	2-valve pushrod
	3.5 <sup>(6)</sup> - 2.5 <sup>(6)</sup>	2.57 (3.5) - 1.84 (2.5)	3.5: 5000 - 6000 2.5: 4500 - 5500	1	85 cc	Manual	2.15:1	Tiller	n/a	4	17 kg	3.5: 381 mm (S) - 508 mm (L) 2.5: 381 mm (S)	2-valve
<b>MARINER VERADO</b>													
300 - 350	Verado 350 - Verado 300	261 (350) - 221 (300)	5800 - 6400	6 (in-line)	2598 cc	Electric (turn-key)	1.85:1	Electro-hydraulic power steering with integral hydraulic cylinder	Fully regulated belt-driven 70 amp (882 watt)	SmartCraft - programmable power trim and tilt	303 kg - 288 kg	635 mm (XL) <sup>(7)</sup>	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control

For more information on the propeller that is right for you, please see your dealer.  
 Fuel requirements: FourStroke and Verado: Unleaded 90 RON min. 300 Verado: Unleaded 98 RON recommended for maximum performance.  
 Gear shift: Forward (F), Neutral (N), Reverse (R), except F2.5 - F3.5:F-N.

(1) Model offering may vary from one of country to another. Please see your local dealer for specific information. (2) Measured at propshaft in accordance with ICOMIA 28.  
 (3) Requires rectifier to complete installation manual versions. Standard on 5 Sailmate model. (4) Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller. (5) Integrated fuel tank 1.1 litre. (6) Integrated fuel tank 0.95 litre. (7) Counter rotation available on XL models.



E. P. Barrus Ltd., Glen Way, Launton Road, Bicester, Oxfordshire, OX26 4UR  
 Tel: 01869 326403 Fax: 01869 363673 marine@barrus.co.uk



The Power Behind The Brands **BARRUS** www.barrus.co.uk